

130 S McKinley Ave Fort Lupton, CI 80621 303-857-6694 www.fortlupton.org



Inspection Line (970)305-3161

2020 Roofing Regulations

I-CODES: 2012 NEC: 2020 2006 IECC

Building Permit shall be posted on house prior to starting work. Any work started prior to obtaining a permit will be subject to additional fees.

For Residential Roof Assemblies see sec. R901-R907 in the 2012 IRC

Contractor Licensing:

\$100,000.00 combined single limit liability insurance required. Certificate of insurance shall be submitted at time of application. The certificate shall identify the limits of the insurance, policy number, and name of insurance company, effective date, and expiration of the policy.

Also, a copy of an endorsement requiring ten day's advance written notice to the City of Fort Lupton in the event of cancellation.

Design Criteria:

Table R301.2(1)											
Climatic and Geographic Design Criteria											
Ground	Wind Design		Seismic	Subjec	ct to Damag	ge From	Winter	Ice Barrier	Flood	Air	Mean
Snow Load	Speed (mph)	Topographic Effects	Design Category	Wintering	Frost Line Depth	Termite	Design Temp	Underlayment Required	Hazard	Freezing Index	Annual Temp
30 psf	115	No	В	Severe	30 in	Slight to Moderate	1	No	*	1000	45 ^o F

*Ice Barrier **IS NOT REQUIRED.** Drip Edge per section R905.2.8.5

<u>Tear-off</u>: All roofing materials shall be removed prior to new application (except one (1) layer of asphalt shingles is allowed to have an additional layer of asphalt shingles applied.) Replace damaged or questionable roof sheathing.

<u>Underlayment:</u> Roofs with 4:12 and greater slopes shall be minimum 1-layer. 2:12 to 4:12 slope shall be 2-layer. Less than 2:12 slope requires modified bitumen. Low slope patio covers, and accessory buildings require modified bitumen if dimensional shingles are used to match shingles on principle building.

Roof covering: Replace damaged roof jacks and vents. Add roof vents where needed to meet code. Sec. R806.

<u>Fasteners:</u> Per manufacturer's installation instructions and ASTM F 1667 to meet 115 Ultimate Wind Exposure C.

<u>Inspections:</u> A mid-roof inspection **ONLY** required for commercial roof assemblies. Permit Card must be available for inspector. **Contractor is required to provide a secured ladder for the inspector**. PRIOR to calling for inspections clean up all debris in yard and roof and clean out gutters and downspouts.

^{***}Repair or replacement of less than 1 square (100 sq ft) of shingles does not require a building permit.